











BT-ANGLE EXACT

Cordless nutrunners

- ▶ Precision Shut-off clutch exceeds ISO tolerance of ±10%
- ▶ Lightweight
- ▶ Broad torque range
- ▶ Trigger repeat protection
- ▶ LED/audible battery charge indicator; same as T-grip
- ▶ LED/audible shut-off indicator; same as T-grip (sent via Bluetooth to controller)
- ▶ Bright LED light for work area illumination
- ▶ All models feature trigger hand forward/reverse control
- ▶ Tools share many common parts
- ▶ Color rings are used to identify joint types on the assembly line
- ▶ Protective rubber cover available for angle heads
- ▶ Uses same batteries/chargers as T-Grip models
- ▶ All models can be hung from balancer using suspension hook
- ▶ All Bluetooth models require wireless EXAConnect controller
- ▶ Tool weight with angle head and battery is 1.6kg/3.5 lbs (BT-ANGLE EXACT 17, 23, 30: 2.6kg/5.7 lbs)

	Order number	Torque on hard joint per ISO 5393 (Nm)	Torque on soft joint per ISO 5393 (Nm)
BT-ANGLE EXACT 2 Bluetooth enabled 	0 602 491 647	0.7 – 2 (0.5 – 1.5 ft.-lbs.)	0.7 – 2 (0.5 – 1.5 ft.-lbs.)
BT-ANGLE EXACT 3 Bluetooth enabled 	0 602 491 656	0.7 – 3 (0.5 – 2.2 ft.-lbs.)	0.7 – 3 (0.5 – 2.2 ft.-lbs.)
BT-ANGLE EXACT 6 Bluetooth enabled 	0 602 491 652	1.5 – 6 (1.1 – 4.4 ft.-lbs.)	1.5 – 6 (1.1 – 4.4 ft.-lbs.)
BT-ANGLE EXACT 7 Bluetooth enabled 	0 602 491 669	2 – 7 (1.5 – 5.1 ft.-lbs.)	2 – 7 (1.5 – 5.1 ft.-lbs.)
BT-ANGLE EXACT 8 Bluetooth enabled 	0 602 491 651	2 – 9 (1.5 – 6.7 ft.-lbs.)	2 – 8 (1.5 – 5.9 ft.-lbs.)
BT-ANGLE EXACT 15 Bluetooth enabled 	0 602 491 650	2 – 15 (1.5 – 11 ft.-lbs.)	2 – 15 (1.5 – 11 ft.-lbs.)
BT-ANGLE EXACT 17 Bluetooth enabled 	0 602 491 675	6 – 17 (4.4 – 12.5 ft.-lbs.)	6 – 13 (4.4 – 9.6 ft.-lbs.)
BT-ANGLE EXACT 23 Bluetooth enabled 	0 602 491 673	7 – 23 (5.1 – 17 ft.-lbs.)	7 – 20 (5.1 – 14.8 ft.-lbs.)
BT-ANGLE EXACT 30 Bluetooth enabled 	0 602 491 671	8 – 30 (5.9 – 22.1 ft.-lbs.)	8 – 28 (5.9 – 20.7 ft.-lbs.)

C-EXACT	EXACT	BT-EXACT	SEC-EXACT	ACCESSORIES
---------	-------	-----------------	-----------	-------------

No-load speed (min ⁻¹)	Angle head	Battery specifications	Direction of rotation	Weight (kg / lbs)	Features	Included accessories
110	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook light-green marking ring
420	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook light-green marking ring
650	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook black marking ring
110	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook orange marking ring
420	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook orange marking ring
250	–	9.6 V (Not included)	R/L	1.0 / 2.2	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook red marking ring
560	–	14.4 V (Not included)	R/L	1.5 / 3.3	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook white color ring
320	– requires HD angle head	14.4 V (Not included)	R/L	1.5 / 3.3	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook orange color ring
220	– requires HD angle head	14.4 V (Not included)	R/L	1.5 / 3.3	Class 2 Blue-tooth module	Torque adjustment tool Housing wrench Suspension hook red color ring